## **MATERIAL SAFETY DATA SHEET**

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Multi-Clean Poli-Mirro Floor Finish

Product Class: Wood floor varnish

800-255-3924 Emergency Telephone Number: Telephone Number for Information: 651-481-1900

Manufacturer's Name and Address:

Multi-Clean®, A Division of Minuteman International, Inc.

600 Cardigan Road Shoreview, MN 55126

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity): Chemical Common Name(s) Mineral spirits 30 - 60 CAS #8052-41-3 Oil modified polyurethane resin В 30 - 60

(proprietary)

SECTION III - HAZARDS IDENTIFICATION

**Emergency Overview** 

Appearance and Odor: Amber liquid, solvent odor.

Primary Hazards: Harmful or fatal if swallowed. Vapor may be harmful. Combustible.

Irritant

**Potential Health Hazards** 

Route(s) of Entry: Skin Absorption: X Inhalation: Ingestion: Х

May cause irritation on contact. Eye: Skin: May cause irritation on contact. Ingestion: May be harmful if swallowed. Inhalation: Vapor may be harmful.

Signs and Symptoms of Exposure: Eyes and Skin: Irritation, redness. Inhalation:

Irritation, central nervous system effects (dizziness, headaches, nausea, etc.). Carcinogenicity: NTP? No IARC Monographs?

OSHA Regulated? No

Target Organ (s): Skin, eyes, respiratory system and central nervous system.

Medical Conditions Generally Aggravated by Exposure: Skin and respiratory

(asthma-like) conditions.

Health Hazards, Chronic: Reports have associated repeated or prolonged occupational exposure to solvents with permanent brain and central nervous system damage (sometimes referred to as Solvent or Painters Syndrome).

**SECTION IV - FIRST AID MEASURES** 

**Emergency and First Aid Procedures:** 

If Swallowed: Do not induce vomiting. Call a physician immediately. Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. Inhalation: If ill effects occur from breathing vapors, remove victim to fresh air and quiet and keep warm.

Raw material data, general toxicology from the trade for similar Sources Used:

UEL 10.%

products.

**SECTION V - FIRE FIGHTING MEASURES** 

Flammability: Combustible Flash Point (method used): Autoignition Temperature: N. Ap

104°F (40°C) PMcc

Flammable Limits: N. Av. LEL .7%

**Extinguishing Media** Water? Water Fog? Foam? X CO<sub>2</sub>? X Dry Chemical? Alcohol Foam?

Vaporizing Liquid? X Other?

Special Fire Fighting Procedures: Exclude air. Water hose stream may spread fire.

Use water spray to keep containers cool.

Unusual Fire and Explosion Hazards: TDG Flammability Classification: Not k
Sensitivity to Mechanical Impact: None Not known

Sensitivity to Static Discharge: Normal, for combustible liquid.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:

Extinguish all sources of possible ignition (flames, sparks, pilot lights, etc.) and provide ventilation. Dike and contain spill with inert material (sand, earth, etc). Collect spill with absorbent material (example: floor-dri). Wash affected area with soap and water.

**SECTION VII - HANDLING AND STORAGE** 

Precautions to be Taken in Handling and Storing:

Normal care in handling and storage. Do not store near heat or open flame.

Other Precautions: Keep out of reach of children.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not normally required

Ventilation: Local Exhaust: Not required Special: Not required Mechanical (General): Ventilate to maintain vapor level below TLV & PEL (listed in Section XI) Other: Not required

Protective Gloves: Natural rubber or synthetic.

Eye Protection: Approved safety goggles or glasses. Footwear: Not required

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not use in food handling or storage areas when food

is present.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Mineral spirits 232-390°F (162-199°C) pH: N. Ap. Specific Gravity (H20) = 1: 861 % Volatile: 60

Vapor Density (Air = 1): > 1 Evaporation Rate (Butyl Acetate = 1): < 1

Solubility in Water: Negligible Vapor Pressure (MM HG): N. Av.

Melting Point:

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable:

Conditions to Avoid: N. Ap.

Incompatibility (materials to avoid): Strong oxidizers

Hazardous Decomposition or By-products: N. Av.

Hazardous Polymerization: May occur: Will not occur: X

Conditions to Avoid: N An

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical OSHA PEL ACGIH TLV LD50 LC50

100 ppm 100 ppm 34,600 mg/kg 21,400 mg/M3 (4 hr.) В N. Ap. N. Ap. N. Av. N Av N Av

Odor Threshold: N. Av.

Coefficient: N. Av.

Oil/Water Distribution

Teratogen, Mutagen, Reproductive Toxin Status: No

Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av. Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state and federal regulations.

(Incineration in an EPA authorized site is recommended) RCRA Hazard Class: D001, Characteristic flammable

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: paint (class 3.3)

UN Number: 1263 Packing Group: III

**SECTION XV - PREPARATION DATA** 

Prepared By: James Tracy

**Telephone Number:** 651-481-1900

Date: 3/02

SECTION XVI - REGULATORY INFORMATION

**US Federal Regulations** 

TSCA Status: All ingredients listed. CERCLA Reportable Quality: None

SARA Title III

Section 302 Extremely Hazardous Chemicals: None

Section 311/312 Hazard Category: Immediate health, chronic health, fire.

Section 313 Toxic Chemicals: None

State Regulations

NOTICE STATE OF CALIFORNIA

Warning: This product may contain chemicals known to the State of California to cause cancer or reproductive defects as trace impurities in the standard industrial materials used in the manufacture of this product.

International Regulations

WHMIS Controlled Product Hazard Class: B2

**SECTION XVII - OTHER INFORMATION** 

None

N. Ap. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

1 A. Health Hazard

2 A. Fire Hazard

0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.