SAFETY DATA SHEET



1. Identification

Product identifier	WINDO-CLEAN+
Other means of identification	
SDS number	578N-66A
Product code	HIL00802
Recommended use	Window Cleaner
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/	Distributor information
Manufacturer	
Company name	HILLYARD INDUSTRIES
Address	302 North Fourth St.
	St. Joseph, MO 64501

Contact person	Regulatory Affairs
Telephone number	(816) 233-1321 (Ext. 8285)
Fax	(816) 383-8485
E-mail	regulatoryaffairs@hillyard.com
Emergency telephone #	(800) 424-9300
	(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements

Signal word Hazard statement

Precautionary statement Prevention Flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Warning

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent), then offer clean, dry container for recycling or reconditioning.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butoxyethanol		111-76-2	10 - < 20
Isopropyl Alcohol		67-63-0	5 - < 10
Propylene glycol monomethyl ethe	r	107-98-2	5 - < 10
Sodium laureth (n=>3) sulfate		9004-82-4	1 - < 3
Other components below reportabl	e levels		60 - < 70

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Propylene glycol monomethyl ether (CAS 107-98-2)	STEL	100 ppm	
101 00 2)			

US.	NIOSH:	Pocket	Guide to	Chemical	Hazards
-					_

US. NIOSH: Pocket Guid Components	e to Chemical Hazards Type		Va	lue
Butoxyethanol (CAS 111-76-2)	TWA		24	mg/m3
,			5 p	pm
Isopropyl Alcohol (CAS 67-63-0)	STEL		122	25 mg/m3
			500) ppm
	TWA		980) mg/m3
			400) ppm
Propylene glycol monomethyl ether (CAS 107-98-2)	STEL		540) mg/m3
			150) ppm
	TWA		360) mg/m3
			100) ppm
ological limit values				
ACGIH Biological Expos Components	ure Indices Value	Determinant	Specimen	Sampling Time
Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
* - For sampling details, pl	ease see the source docu	iment.		
posure guidelines				
US - California OELs: Sk	in designation			
Butoxyethanol (CAS 1	11-76-2) omethyl ether (CAS 107-9	98-2) Can be	absorbed throug absorbed throug	
Butoxyethanol (CAS 1	11-76-2)		signation applie	S.
US - Tennessee OELs: S	-			
US NIOSH Pocket Guide	nol (CAS 111-76-2) Can be absorbed through the skin. ket Guide to Chemical Hazards: Skin designation			
Butoxyethanol (CAS 1 US. OSHA Table Z-1 Lim			absorbed throug	gh the skin.
Butoxyethanol (CAS 1				ah the skin
propriate engineering ntrols	Good general ventila applicable, use proc maintain airborne lev	76-2) Can be absorbed through the skin. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
dividual protection measur Eye/face protection	es, such as personal pr	, such as personal protective equipment Wear safety glasses with side shields (or goggles).		
Skin protection				
Hand protection	For prolonged or rep	eated skin contact	use suitable pro	tective gloves.
Other	None normally requi impervious clothing.	None normally required. If unable to avoid prolonged or repeated contact with skin, wear		
Respiratory protection Thermal hazards	In case of insufficien None known.	t ventilation, wear	suitable respirate	ory equipment.
eneral hygiene nsiderations	When using do not s after handling the ma	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
. Physical and chemic	C .			

9 ıy μ ľ

Clear, dark purple liquid

Physical state	Liquid.
Form	Liquid.
Color	Dark purple
Odor	Mild solvent odor
Odor threshold	Not available
рН	6 - 8
Melting point/freezing point	Not available
Initial boiling point and boiling range	184 °F (84.44 °C) corr.
Flash point	> 101.0 °F (> 38.3 °C) Closed Cup
Evaporation rate	< 1 Ethyl ether = 1
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	17.5 mm Hg
Vapor density	1.5 Air=1
Relative density	0.98 at 77°F
Solubility(ies)	
Solubility (water)	100 % Complete
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	8.15 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	> 97 %
VOC	30 %
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion
Information on likely routes of e	
Inhalation	Harmful if inhaled.
Skin contact	Harmful in contact with skin. Causes skin irritation.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Acute toxicity	Harmful if inhaled. Harmful in contact with skin.			
Components	Species	Test Results		
Isopropyl Alcohol (CAS 67-63-0)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	12800 mg/kg		
Propylene glycol monomethyl eth	er (CAS 107-98-2)			
<u>Acute</u>				
Dermal				
LD50	Rabbit	13 g/kg		
Inhalation				
LC50	Rat	54.6 mg/l, 4 Hours		
Oral				
LD50	Rat	5.71 g/kg		
* Estimates for product may I	be based on additional component data	i not shown.		
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Causes serious eye irritation.			
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
IARC Monographs. Overall	Evaluation of Carcinogenicity			
Butoxyethanol (CAS 111 OSHA Specifically Regulated	-76-2) 3 No ed Substances (29 CFR 1910.1001-10	ot classifiable as to carcinogenicity to humans. 252)		
Not regulated.				
Not listed.	ogram (NTP) Report on Carcinogens			
Reproductive toxicity	This product is not expected to caus	e reproductive or developmental effects		
Specific target organ toxicity -	This product is not expected to cause reproductive or developmental effects. Not classified.			
single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not an aspiration hazard.			
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful.			
	Butoxyethanol may be absorbed throp prolonged. These effects have not be	ough the skin in toxic amounts if contact is repeated and been observed in humans.		
12. Ecological informatio	n			

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environmer		
Product		Species	Test Results
WINDO-CLEAN+			
Aquatic			
Crustacea	EC50	Daphnia	97.5242 mg/l, 48 hours estimated

Product		Species	Test Results
Fish	LC50	Fish	2047.5298 mg/l, 96 hours estimated
Components		Species	Test Results
Butoxyethanol (CAS 11	1-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Isopropyl Alcohol (CAS	67-63-0)		
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affini	s) > 1400 mg/l, 96 hours
Sodium laureth (n=>3) s	sulfate (CAS 9004	-82-4)	
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	2.43 - 4.01 mg/l, 48 hours
* Estimates for product	may be based on	additional component data not shown.	
sistence and degradab	ility No data is	s available on the degradability of this produc	t.
accumulative potential			
Partition coefficient n-	octanol / water (log Kow)	
Butoxyethanol		0.83	
Isopropyl Alcohol		0.05	
bility in soil	No data a	vailable.	
ner adverse effects	The produpotential.	uct contains volatile organic compounds which	n have a photochemical ozone creation
. Disposal consider	ations		
nosal instructions	Collect ar	nd reclaim or dispose in sealed containers at l	icensed waste disposal site. Do not

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Waste from normal product use may be sewered to a public owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

IA	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Isopropyl Alcohol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	111
Environmental hazards	No.
ERG Code	128
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.

Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Isopropyl Alcohol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Not available.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	
IATA; IMDG	



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US federal regulations

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation
	Serious eye damage or eye irritation

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
 Not regulated.

 Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
 Not regulated.

 Safe Drinking Water Act Not regulated.
 (SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace Isopropyl Alcohol (CAS 67-63-0) Low priority

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butoxyethanol (CAS 111-76-2) Isopropyl Alcohol (CAS 67-63-0) Propylene glycol monomethyl ether (CAS 107-98-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	01-29-2015
Revision date	08-25-2016
Version #	02
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
Disclaimer	No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products. HILLYARD cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.