according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 35000003598 SITE_FORM Number 300000000000002940.002

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Trade name	SC JOHNSON® PASTE WAX	
Use of the Substance/Mixture	Furniture Polish/Cleaner	
Company	S.C. Johnson & Son, Inc. 1525 Howe Street Racine WI 53403-2236	
Emergency telephone number	24 Hour Medical Emergency Phone: (866)23 24 Hour International Emergency Phone: (70 24 Hour Transport Emergency Phone: (800)	03)527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview Appearance / Odor	:	opaque / solid / solvent-like
Immediate Concerns	:	Warning FLAMMABLE: Keep away from heat, sparks and flame. Avoid contact with skin, eyes and clothing.
Potential Health Effects Exposure routes	:	Eye, Skin, Inhalation, Ingestion.
Eyes	:	No adverse effects expected when used as directed.
Skin	:	Prolonged or repeated contact may dry skin and cause irritation. May cause skin reactions in rare cases.
Inhalation	:	Excessive exposures may affect human health, as follows: Causes headache, drowsiness or other effects to the central nervous system.
Ingestion	:	May cause abdominal discomfort. Causes headache, drowsiness or other effects to the central nervous system.
Aggravated Medical Condition	:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc. may be more susceptible to irritating effects
		1/8

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous chemicals present at or above reportable levels as defined by OSHA 29 CFR 1910.1200 or the Canadian Controlled Products Regulations are listed in this table:

Chemical Name	CAS-No.	Weight percent
Stoddard solvent	8052-41-3	60.00 - 100.00
Paraffin waxes and Hydrocarbon waxes	8002-74-2	10.00 - 30.00
Carnauba wax	8015-86-9	5.00 - 10.00
1,2,4-Trimethylbenzene	95-63-6	1.00 - 5.00

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES			
Eye contact	:	Rinse with plenty of water. Get medical attention if irritation develops and persists.	
Skin contact	:	Wash off with soap and water.	
Inhalation	:	Remove to fresh air. If breathing is affected, get medical attention.	
Ingestion	:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.	
5. FIREFIGHTING MEASURES	;		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.	
Specific hazards during firefighting	:	Do not use a solid water stream as it may scatter and spread fire.	
Further information	:	Cool and use caution when approaching or handling fire- exposed containers. For large quantities of flammable liquids, consider containment to prevent the spread of fire. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.	
2/8			

Material Safety Data Shee according to ANSI Z400.1- 2004 and 29 0		
SC JOHNSON® PAST	ΕV	VAX
Version 2.0		Print Date 02/01/2012
Revision Date 01/10/2012		MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002
Flash point	:	31.1 °C 87.98 °F Method: Tag Closed Cup (TCC)
Lower explosion limit	:	Note: no data available
Upper explosion limit	:	Note: no data available
6. ACCIDENTAL RELEASE ME	ASU	IRES
Personal precautions		Remove all sources of ignition. Wear personal protective equipment.
Environmental precautions	:	Outside of normal use, avoid release to the environment.
Methods for cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Use only non-sparking equipment. Dike large spills. Clean residue from spill site.
7. HANDLING AND STORAGE		
Handling		
Advice on safe handling	:	Avoid breathing vapors, mist or gas. KEEP OUT OF REACH OF CHILDREN AND PETS.
Advice on protection against fire and explosion	:	Keep away from heat and sources of ignition. Take measures to prevent the build up of electrostatic charge.
Storage		
Requirements for storage areas and containers	:	Keep in a dry, cool and well-ventilated place.
		3/8

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Stoddard solvent	8052-41-3	2,900 mg/m3	500 ppm	-	OSHA TWA
Stoddard solvent	8052-41-3	-	100 ppm	-	ACGIH TWA
Paraffin waxes and Hydrocarbon waxes	8002-74-2	2 mg/m3	-	-	ACGIH TWA

Personal protective equipment

Respiratory protection

Industrial setting	:	Use only with adequate ventilation.
Household setting	:	Use only with adequate ventilation.
Hand protection	:	For prolonged or repeated contact use protective gloves.
Eye protection		
Industrial setting	:	If prolonged or repeated contact is possible: Safety glasses with side-shields
Household setting	:	Avoid contact with eyes.
Skin and body protection	:	No special requirements.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:	solid
Color	:	opaque
Odor	:	solvent-like

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

рН	:	not applicable	
Boiling point	:	no data available	
Freezing point	:	not applicable	
Flash point	:	31.1 °C 87.98 °F Method: Tag Closed Cup (TCC)	
Evaporation rate	:	no data available	
Flammability (solid, gas)	:	no data available	
Autoignition temperature	:	no data available	
Lower explosion limit	:	no data available	
Upper explosion limit	:	no data available	
Vapour pressure	:	no data available	
Density	:	6.52 g/cm3 at 25 °C	
Water solubility	:	negligible	
Partition coefficient: n- octanol/water	:	no data available	
Viscosity, dynamic	:	not applicable	
Viscosity, kinematic	:	not applicable	
Volatile Organic Compounds Total VOC (wt. %)*	:	80 % - additional exemptions may apply *as defined by US Federal and State Consumer Product Regulations	
10. STABILITY AND REACTIVITY	1		
Conditions to avoid	:	Heat, flames and sparks.	
Materials to avoid	:	Strong oxidizing agents	
Hazardous decomposition products	:	Thermal decomposition can lead to release of irritating gases and vapours.	
Hazardous reactions	:	Stable under recommended storage conditions.	
5/8			

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

TOXICOLOGICAL INFORM	IATION
Acute oral toxicity	: LD50 estimated > 5,000 mg/kg
Acute inhalation toxicity	: no data available
Acute dermal toxicity	: No adverse effects expected when used as directed.
Chronic effects Carcinogenicity	: no data available
Mutagenicity	: None Anticipated
Reproductive effects	: no data available
Teratogenicity	: no data available
Sensitisation	: no data available
2. ECOLOGICAL INFORMAT	ION
Ecotoxicity effects	: no data available
3. DISPOSAL CONSIDERAT	ONS
	Observe all applicable Federal, Provincial and State regulations and Local/Municipal ordinances regarding disposal. Consumer may discard empty container in trash, or recycle where facilities exist.
RCRA waste class	: D001 (Ignitable Waste)
	6/8

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

14. TRANSPORT INFORMATION

Land transport

Land transport	
 U.S. DOT and Canadi Proper shipping name Class: UN number Packaging group: Note: 	ian TDG Surface Transportation: UN 1325 Flammable Solid, Organic, N.O.S., 4.1, II 4.1 1325 II Limited quantities derogation may be applicable to this product, please check transport documents.
Sea transport	
 IMDG: Proper shipping name Class: UN number: Packaging group: EmS: Note: 	UN 1325 Flammable Solid, Organic, N.O.S., 4.1, II 4.1 1325 II F-A, S-G Limited quantities derogation may be applicable to this product, please check transport documents.
Air transport	
 ICAO/IATA: Proper shipping name Class: UN/ID No.: Packaging group: Note: 	UN 1325 Flammable Solid, Organic, N.O.S., 4.1, II 4.1 UN 1325 II SC Johnson typically does not ship products via air, therefore it has not been determined if the product container meets current IATA/ICAO package criteria. Refer to IATA/ICAO Dangerous Goods Regulations for detailed instructions when shipping this item by air.
15. REGULATORY INFORMAT	ΓΙΟΝ
Notification status	: All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA)

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

16. OTHER INFORMATION

HMIS Ratings

Chemical Substance Inventory.

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



SC JOHNSON® PASTE WAX

Version 2.0

Revision Date 01/10/2012

Print Date 02/01/2012

MSDS Number 350000003598 SITE_FORM Number 300000000000002940.002

Health	1	
Flammability	3	
Reactivity	0	

NFPA Ratings		
Health	1	
Fire	3	
Boostivity	0	
Reactivity	0	
Special	_	
Opecial		

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by:	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)