

**MATERIAL SAFETY DATA SHEET****NFPA RATING:** Health= 2 Flammability = 0 Reactivity = 0**\*HMIS RATING:** Health= 2 Flammability = 0 Physical Hazard = 0**SECTION I -- IDENTITY AND MANUFACTURER'S INFORMATION**

\*(540N-22A)

**Manufacturer's Name:** HILLYARD INDUSTRIES**Product Name:** DEVASTATOR**Address:** 302 North Fourth Street  
St. Joseph, MO 64501**Date Prepared:** March 23, 2011 (Version 3)**Prepared by:** Regulatory Affairs Department**Emergency Telephone No.:** (800) 424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)**Other information calls:** (816) 233-1321 (Ext. 8285)<http://www.hillyard.com>**SECTION II -- INGREDIENTS/IDENTITY INFORMATION****Components****(Specific Chemical Identity:**

Common Name(s)	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
2-Butyl cellosolve (2-Butoxyethanol)(1)*	111-76-2	50 ppm	20 ppm	N.A.	20-25
Ethanolamine (2)	141-43-5	3 ppm	3 ppm	N.A.	5-10
Water	7732-18-5	none	none	N.A.	---
Benzyl alcohol	100-51-6	not established	not established	N.A.	---
Sodium xylene sulfonate	1300-72-7	not established	not established	N.A.	---

(1) Regulated by OSHA: CA, FL, ID, IL, LA, MA, MN, NJ, PA, RI, WA.

(2) Regulated by OSHA,: CA, CT, FL, ID, IL, LA, MA, ME, MN, NJ, PA, RI, WA, WI.

\*This product contains the following chemicals subject to the reporting requirements of SARA Title III, Sec. 313, and 40 CFR Part 372: 2-Butoxyethanol.

VOC = 945 gm./l

**\*SECTION III -- PHYSICAL / CHEMICAL CHARACTERISTICS****Boiling Point:** 210°F**Specific Gravity (H<sub>2</sub>O = 1):** 25°C = 1.0 **\*Density =** 8.32 lbs/gal**Vapor Pressure (mm Hg.):** 16.0**\*Percent Volatile by Volume (%):** 98 – 99%**Vapor Density (AIR = 1):** 1.6**Evaporation Rate (ethyl ether = 1):** slower than 1**Solubility in Water:** appreciable**\*Appearance and Odor:** clear, colorless liquid, mild solvent odor**\*pH (concentrate) =** 11.25 – 12.25**SECTION IV -- FIRE AND EXPLOSION HAZARD DATA****Flash point:** none (Tag Closed Cup) **Flammable Limits:** LEL = N/A UEL = N/A**Extinguishing Media:** Carbon dioxide, dry chemical or foam (water spray to cool closed containers)**Special Fire Fighting Procedures:** Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. **Unusual Fire and Explosion Hazards:** None known to Hillyard.**SECTION V -- PHYSICAL HAZARDS****Stability:** Stable**Conditions to Avoid:** N/A**Incompatibility (Materials to Avoid):** Keep away from strong oxidizers such as permanganate or strong oxides.**Hazardous Decomposition Products or Byproducts:** As with any organic material, combustion will produce carbon dioxide and carbon monoxide.**Hazardous Polymerization:** Will not occur **Conditions to Avoid:** N/A**SECTION VI -- HEALTH HAZARD DATA****Routes of entry:** Inhalation? Yes Skin? Yes Ingestion? Yes**HEALTH HAZARDS (1. Acute and 2. Chronic)**

1. According to Primary Skin Irritation Test (FHSA), product concentrate is moderate irritant to skin at 24 hours. Eye Irritation Test (FHSA) = corrosive. When tested as specified this product was not considered to be a UN/DOT corrosive at 4 hours. Acute oral limit test showed the product was orally toxic at 5g./kg. It may be harmful or fatal if swallowed. Inhalation of fine fog mist can cause irritation to mucous membranes. Fine fog mist application is not recommended. 2. None known to manufacturer.

## SECTION VI -- HEALTH HAZARD DATA continued

**Chemical listed as Carcinogen or Potential Carcinogen:**

**National Toxicology Program** = No    **I.A.R.C. Monographs** = No    **OSHA** = No

**Signs and Symptoms of Exposure:** Butyl cellosolve is readily absorbed through the skin in toxic amounts. Inhalation of high concentrations of vapors results in respiratory and eye irritation, narcosis, headache, nausea, dizziness, hematuria and damage to liver and kidneys.

**Medical Conditions Generally Aggravated by Exposure:** Repeated overexposure may result in damage to the blood.

**Emergency and First Aid Procedures:** **Inhalation:** Remove person to fresh air. If breathing difficulty persists or occurs later, call physician. **Eyes/Skin:** In case of eye or skin contact, immediately flush eyes or skin with plenty of water for 15 minutes. Get prompt medical attention. Remove and wash all contaminated clothing before reuse.

**Ingestion:** If swallowed, immediately give large amounts of water and IMMEDIATELY CALL A PHYSICIAN, hospital emergency room or poison control center.

## \*SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

**Steps To Be Taken In Case Material Is Released Or Spilled:** Absorb large spills with floor dry material (see disposal below). Small spills: Flush with water and pick up with mop or wet vacuum.

**Waste Disposal Method:** Dispose of in accordance with state or local regulations. Do not dispose of in storm drains or streams; monoethanolamine is toxic to fish.

**Precautions To Be Taken In Handling And Storing:** Keep container closed when not in use. Since empty packages retain product residue, follow label warning even after package is empty. Do not store above 120°F. Vapors may produce respiratory irritation or damage and increase susceptibility to respiratory illness. USE WITH ADEQUATE VENTILATION. Avoid prolonged breathing of vapors. Open windows and doors, use exhaust fans or other means to insure fresh air entry during application and drying. Refer to OSHA Standard 29 CFR 1910.94 for technical guidelines on keeping air contamination below acceptable exposure limits. Do not get on skin, in eyes or on clothing.

## SECTION VIII -- CONTROL MEASURES

**Respiratory Protection (Specify Type):** Wear appropriate, properly fitted respirator (NIOSH or MSHA approved unless air monitoring demonstrates vapor or mist levels are below applicable limits.

**Ventilation:** at least 10 air changes per hour recommended

**Local Exhaust** = recommended    **Mechanical (General)** = recommended    **Special** = N/A    **Other** = N/A

**Protective Gloves:** impervious rubber gloves recommended    **Eye Protection:** chemical safety goggles

**Other Protective Clothing or Equipment:** protective clothing

**Work / Hygienic Practices:** Wash contaminated clothing before reuse (including shoes).

## SECTION IX - TRANSPORTATION INFORMATION

**Applicable regulations:** DOT = No; IMCO = No; IATA = No

**Proper shipping name:** Cleaning compound

**UN No.:** not applicable    **Limited Qty.:** not applicable    **Hazard Class:** not applicable

**Labels required:** not required    **DOT Exception:** not applicable

**EPA Hazardous waste/number code:** not listed

**Hazardous waste characteristics:**

**Ignitability** = not applicable; **Corrosivity** = not applicable; **Reactivity** = not applicable

### DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.