ILOVETOCREATE®

Safety Data Sheet



1. COMPANY AND PRODUCT IDENTIFICATION

iLoveToCreate A Duncan Enterprises Company

5673 East Shields Avenue Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

EMERGENCY TELEPHONE NUMBERS Health Emergencies: 559-291-4444 7:00 am – 3:30 pm Pacific Std. Time Spill and Off-Hour Health Emergencies: 800-424-9300 U.S. and Canada 703-527-3887 Outside U.S. and Canada (Collect)

Product Name:ALEENE'S ORIGINAL TACKY GLUEProduct Description:Water-Based Adhesive

2. HAZARDS IDENTIFICATION

1	0 M ² · · · · · ·
	0 = Minimal
0	1 = Slight
0	2 = Moderate
See Section 8	3 = Serious 4 = Severe * = Chronic Effects
	0 See

Emergency Overview	Not considered as hazardous
Eye Contact:	Slight / mild irritant
Skin Contact:	Repeated or prolonged skin contact may result in mild irritation
Inhalation:	Vapor may be an irritant to respiratory tract
Ingestion:	Ingestion may cause irritation of the gastrointestinal tract

3. COMPOSITION / INGREDIENT INFORMATION

Chemical Family:	Water based polymer emulsion	
Component	CAS Number	Concentration %
None Hazardous		

4. FIRST AID MEASURES

Eye	Flush eyes with large amounts of water until irritation subsides. Consult a physician
Contact:	if irritation persists.
Skin	Wash affected skin areas thoroughly with soap and water. Consult a physician if
Contact:	irritation persists.
Inhalation:	Move subject to fresh air. Consult a physician if symptoms persist.
Ingestion:	Treat symptomatically and supportively. Get medical attention. DO NOT attempt to give anything by mouth to an unconscious person.

iLoveToCreate Safety Data Sheet – Aleene's Original Tacky Glue

•••••	
Autoignition Temperature:	Not Available
Flash Point:	> 212° F
Upper Explosive Limit (%):	Not Applicable
Lower Explosive Limit (%):	Not Applicable
Extinguisher Media:	CO ₂ , Dry Chemical, Foam – Use extinguishing media appropriate for surrounding fire
Special Firefighting Procedures:	Fire fighters should be equipped with self- contained breathing apparatus to protect against potentially toxic and irritating fumes.
Fire & Explosion Hazards:	This is a water-based product and presents no particular fire or explosion hazard. Dry polymer film will burn. Product contains low level of organic volatiles which may be emitted at elevated temperatures.
NFPA Flammability Hazard Class:	0 = Insignificant

5. FIRE FIGHTING MEASURES

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:	Absorb spillages onto sand, earth or any suitable absorbent material. Sweep up and shovel into waste drums. Wash the spillage area with water. Washings must be prevented from entering surface water drains. Disposal should be in accordance with local, state or national legislation.
For safety and environmenta information.	I precautions, please review entire Safety Data Sheet for necessary

7. HANDLING AND STORAGE

Storage Temperature:	40° - 100°F
Handling / Storage:	Avoid extreme temperatures. Protect from freezing. This material should not be spilled, discharged, or flushed into sewers or public waterways. Product contains low level of organic volatiles which could accumulate in the unvented headspace of drums or bulk storage vessels. Open drums in well ventilated area. Avoid breathing vapors.
Ventilation Requirements:	General

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Conditions Under Which Personal	
Protective Equipment Required:	Normal work conditions, maintenance / repair
Eye Protection Requirements:	Wear safety glasses with side shields; protect against splashing
Glove Requirements:	The use of chemically resistant gloves is recommended.
Clothing Requirements:	Uniforms, coveralls, or a lab coat should be worn. Rubber boots and apron should be worn if exposure is severe.
Change / Removal of Clothing:	Remove contaminated clothing and launder before reuse.
Wash Requirements:	Wash before eating, drinking, or using toilet facilities.
Respirator Requirements:	None required under normal handling conditions. Use NIOSH approved respirator if vapor or mist levels are irritating.
Ventilation Requirements:	General

Pure Material or Mixture:	Mixture
Physical Form:	Liquid
Appearance / Physical Description:	White liquid, slight sweet odor
pH:	4 - 5
Boiling Point:	> 100° C (> 212°F)
Melting / Freezing Point:	Approx. 0°C (32°F)
Odor Threshold:	Not Available
Solubility in Water:	Miscible
Partition Coefficient (n-octanol/water):	Not Applicable
Specific Gravity (Water = 1):	1.08
Bulk Density:	9.0 lb / gal
Volatiles:	Approx. 50% / wt
Vapor Pressure:	17.5 mm Hg @ 20°C (68°F)
Evaporation Rate (Water = 1):	1
Vapor Density (Air = 1):	0.62
Volatile Organic Compounds:	Estimated 0.045 lb/gal
Autoignition Temperature:	Unknown
Flash Point:	> 100° C (> 212°F)
Oxidizing Properties:	Not Applicable

10. STABILITY AND REACTIVITY

Stability:	Stable
Materials to Avoid:	Strong oxidizers, materials that react with water
NFPA Reactivity Class:	0 = Insignificant
Conditions to Avoid:	Protect from temperatures below 40° F
Hazardous Polymerization:	Will not occur

11. TOXICOLOGICAL INFORMATION

Acute (Short-Term) Effects of Exposure	
Route of Entry	Eye contact, skin contact, inhalation, ingestion
Acute Effects – Eye:	Slight, transient
Acute Effects – Skin Contact:	No known signs or symptoms associated with exposure to product
Acute Effects – Inhalation:	No known signs or symptoms associated with exposure to product
Acute Effects – Ingestion:	No known signs or symptoms associated with exposure to product

Chronic (Long-Term) Effects of Exposure		
Effect of Chronic Exposure:	The toxicological properties of this product have not been fully evaluated. Use of good industrial hygiene practices is required. Avoid direct contact with skin or eyes. Do not ingest or inhale. Product is unlikely to cause harmful effects under recommended conditions of handling and use.	
Target Organs:	Not applicable	
Carcinogenicity:	None	

12. ECOLOGICAL INFORMATION

Potential to Bioaccumulate:UnknownAquatic toxicity:None established

iLoveToCreate Safety Data Sheet - Aleene's Original Tacky Glue

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods:	Waste disposal should be in accordance with existing Federal, State, and Local environmental regulations.
Empty Container Warnings:	Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Information	
DOT Shipping Name:	Adhesive Glues, NOI 4620 Sub. 5
DOT Hazard Class:	Non-hazardous
DOT Reportable Quantity:	None

United Nations Information

U.N. Number: U.N. Class: None None

The information provided herein may not include the impact of additional regulatory requirements (e.g., for materials meeting the definition of a hazardous waste under RCRA, hazardous substances under CERCLA, and/or marine pollutants under CWA or other similar federal, state or local laws) or any associated exceptions or exemptions under regulations applicable to the transport of this material.

15. REGULATORY INFORMATION

TSCA:	All components are on the TSCA Inventory	
FDA:	21CFR175.105	
SARA/Title III:	This product contains no substances at or above the reported threshold under Section 313, based on available data.	
CONFORMS TO NONTOXIC Astm D-4236		
CALIFORNIA PRO	OPOSITION 65	
WARNING: This product contains the following chemicals that are known to the State of California to		
cause cancer, birth defects, or other reproductive harm:		
Component	CAS Number	
Formaldehyde (g	as) 50-00-0	
Unless a concentration is specified in Section 2 of the SDS, the above chemical(s) are present in trace		
amounts.		

16. OTHER INFORMATION

Table of Abbreviations		
ACGIH	American Conference of Governmental Industrial Hygienists	
ANSI	American National Standards Institute	
ASTM	American Society for Testing Materials	
°C	Degrees Centigrade	
CAS	Chemical Abstract Service	
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	

16. OTHER INFORMATION (Continued)

	Table of Abbreviations (Continued)	
CFR	Code of Federal Regulations	
CPR	Controlled Products Regulations	
DOT	Department of Transportation	
EPA	Environmental Protection Agency	
°F	Degrees Fahrenheit	
FDA	Food & Drug Administration	
g/l	Grams per liter	
DOT	Department of Transportation	
EPA	Environmental Protection Agency	
°F	Degrees Fahrenheit	
FDA	Food & Drug Administration	
g/l	Grams per liter	
Hg	Mercury	
HMIS	Hazardous Materials Identification System	
IARC	International Agency for Research on Cancer	
LD	Lethal Dose	
mg / kg	Milligram per kilogram	
mm	Millimeter	
SDS	Safety Data Sheet	
MSHA	Mine Safety and Health Administration	
N/A	Not Applicable	
NFPA	National Fire Protection Association	
NIOSH	National Institute for Occupational Safety and Health	
NTP	National Toxicology Program	
OSHA	Occupational Safety and Health Administration	
ppm	Parts per million	
SARA	Superfund Amendment and Reauthorization Act	
STEL	Short-Term Exposure Limit	
TSCA	Toxic Substances Control Act	
TWA	Time - Weighted Average	
U.N.	United Nations	
WHMIS	Workplace Hazardous Materials Information System	
>	Greater Than	
<	Less Than	

Creation Date:	04/06/93
Revision Date:	01/18/13
Technical Contact:	Frank Peters
	Research & Development Manager
	iLoveToCreate
	A Duncan Enterprises Company
	5673 East Shields Avenue
	Fresno, CA 93727
	559-291-4444
	559-291-9444 (Fax)

iLoveToCreate Safety Data Sheet – Aleene's Original Tacky Glue

<u>Disclaimer</u>

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.