

Issue Date: 06/25/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Brighton Professional™ Stainless Steel Cleaner Material name

Material number : BPR142A18-A

Manufacturer or supplier's details

Company : Staples Contract & Commercial, Inc.

Address : 500 Staples Drive

Framingham, MA 01702 USA

1-888-322-0912 Telephone

Emergency : 1-888-322-0912 (24-HRS, 7 DAYS A WEEK)

Note: Products labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations: The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	light cream
Odour	characteristic

GHS Classification

Flammable aerosols : Category 2 Gases under pressure : Liquefied gas : Category 2 Skin irritation Skin sensitisation : Category 1

GHS Label element

Hazard pictograms







Signal word

Hazard statements : H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 1 - < 5
Stoddard solvent	8052-41-3	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Silicon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

			1,800 mg/m3	
butane	106-97-8	TWA	800 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	800 ppm	OSHA P0
			1,900 mg/m3	
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm	OSHA Z-1
			2,900 mg/m3	
		TWA	100 ppm	OSHA P0
			525 mg/m3	

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : light cream
Odour : characteristic
Odour Threshold : no data available
pH : no data available
Melting point/freezing point : no data available
Boiling point : no data available

Flash point :

no data available

Evaporation rate : no data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : no data available
Lower explosion limit : no data available

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

Vapour pressure : no data available
Relative vapour density : no data available
Density : 0.938 g/cm3

Solubility(ies)

Water solubility : partly soluble
Partition coefficient: n- : no data available

octanol/water

Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

Viscosity, kinematic : no data available

Heat of combustion : 15.00 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 rat: > 2,000 mg/kg

propane:

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 658 mg/l Exposure time: 4 h

LC50 rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light:

propane: butane:

Stoddard solvent:

citral:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

Further information

Product:

Remarks: no data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

Components:

butane :

Partition coefficient: n-

octanol/water

citral:

Partition coefficient: n-

octanol/water

: Pow: 2.76

: Pow: 2.89

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: no data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated light:

Additional ecological

information

: no data available

SAFETY DATA SHEET BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

ORM-D, LIMITED QUANTITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard

BRIGHTON STAINLESS STEEL CLEANER

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

: SARA 313: This material does not contain any chemical **SARA 313**

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL This product contains one or several components that are not on the

Canadian DSL nor NDSL.

AICS Not in compliance with the inventory **NZIoC** Not in compliance with the inventory **PICCS** Not in compliance with the inventory Not in compliance with the inventory **IECSC**

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

WHMIS Classification(s):

Class A - Compressed Gas Class B5 - Flammable Aerosol Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:








SECTION 16. OTHER INFORMATION

Further information



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

SAFETY DATA SHEET **BRIGHTON STAINLESS STEEL CLEANER**

(BPR142A18-A)

Version 1.0 Revision Date 06/25/2015

OSHA GHS Label Information:

Hazard pictograms







Signal word Warning:

Hazard statements Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin

irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash fore

occurs: Get medical advice/ atte

reuse.

Storage: Protect from sunlight. 22

Disposal: Dispose of contents/c

Regulatory Specialist, Staples Brand Group, (508) 253-5000 Prepared By:

Always follow label directions carefully when using this or any other chemical product. If information about this product is required, please contact Staples at 1-888-322-0912 or visit our website at www.staplesadvantage.com. Keep Safety Data Sheets filed and organized in an area accessible to workers according to all applicable regulations.

All information contained in this SDS is provided to the best of Staples Contract & Commercial Inc's knowledge. No warranty is made with respect to this information expressed or implied, including warranties of merchantability or fitness for a particular purpose. Users are responsible for verifying the information under their own operating conditions to determine whether the products listed in the SDS are suitable for their intended use. Users are responsible for compliance with all laws and regulations as may be required by their receipt of the information and use of the products provided with this SDS.