

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special- - Manufacturer's Name: AMREP, INC. Address: 990 Industrial Park Drive Marietta, GA 30062	HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): <p style="text-align: center;">MISTY WAX OFF</p>
Date Prepared: 06/27/01 Prepared By: CH/IB Information Calls: (770) 422-2071 EMERGENCY RESPONSE NUMBER: 1(800) 255-3924	MSDS Number: A00807 Revision: 11 <p style="text-align: center;">NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA</p>

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
MONOETHANOLAMINE	141-43-5	No	3	3	d
ISOBUTANE	75-28-5	No	800	800	d
2-BUTOXYETHANOL *	111-76-2	Yes	25 (skin)	20 (skin)	d
*GLYCOL ETHER					

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point: N/A	Specific Gravity (H ₂ O=1): Concentrate Only = 0.990
Vapor Pressure @ 70°F (Aerosols): Max. 60	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E
Solubility in Water: Soluble	Water Reactive: No
Appearance and Odor: Gelled spray with mint and amine fragrance.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA		
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

SECTION 4 - REACTIVITY HAZARD DATA	
STABILITY [X] STABLE [] UNSTABLE	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Strong organic acids, strong mineral acids, alkaline metals and copper.	Conditions to Avoid: Open flame, welding arcs, heat.
Hazardous Decomposition Products: CO, CO ₂ , nitrogen compounds.	

SECTION 5 - HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS	
ACUTE EFFECTS	
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	
Eye Contact: Irritation	Skin Contact: Irritation
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.	
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause nasal & respiratory irritation, diarrhea, vomiting. Lab animals have experienced anemia, liver, kidney, lung, blood damage to Glycol Ether EB.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES	
Eye Contact: Flush with water for 15 minutes, followed by a 1% saline solution. If irritated, seek medical attention.	
Skin Contact: Wash with soap and water. If irritated, seek medical attention.	
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.	
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH to be used in positive pressure mode.	
Protective Gloves: Rubber gloves recommended.	Eye Protection: Safety glasses recommended.
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. Flush small spills to sewer.	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.	
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only